

## Flash And Fire Point By Claveland Open Cup

BB 502

ASTM D.92. D.117. D.803 / AASHTO T.48



BB 502.1



BB 502.2



BB 502.3




BB 502.4



BB 502.5



BG 013/1



BG 056/2



BG 034/6



Flash And Fire Point  
By Claveland Open Cup

There are a number of test methods using different equipment with closed or open cups. The Cleveland flash cup apparatus is used to test cutback bitumen and may sometimes also be used to test penetration grade bitumen. The apparatus utilizes the open cup test method.

Type	Parts Name	Specification	Qty
BB 502.1	Flash cup	Brass. Insulation handle	1 Pc
BB 502.2	Burning Pipe	Brass pipe, insulation handle	1 Pc
BB 502.3	Flash cup plate	Steel plate	1 Pc
BB 502.4	Flash cup plate support	Adjustable height metal, thermometer holder	1 Pc
BB 502.5	Y-Connector	Brass, provided with gas hose	
BG 013/1	Bunsen Burner	Heat resources	1 Pc
BG 056/2	Asbestos wire gauze	15 x 15 cm	1 Pc
BG 034/6	Thermometer	Range 0 – 400 C	1 Pc

**Supplied without :**

- BG.012/2 Kitchen LPG Tube
- BG.045/2 Leather Glove
- BG.011/1 Hot Plate
- BG.036/2 Metal Dial Thermometer 0-300 C
- BG.016/4 Mixing Bowl
- BG.049/9 Spoon