

Field CBR Test

BS 105
ASTM D.4429



Field CBR Test

Type	Parts Name	Specification	Qty
BS 105.1	Mechanical Jack	Cast aluminium housing 5 tons cap, hand operated 2 speeds	1 Set
BS 105.2	Swivel head	Cast aluminium	1 Pc
BS 105.3	Field Penetration Piston	Machined steel plated 3 sq in cross section area	1 Pc
BS 105.4	Extention Set	Machined steel plated 5 cm, 10 cm, 20 cm, 30 cm and 60 cm with connecting adaftor	1 Set
BS 105.5	Reference Beam	Steel pipe 150 cm span	1 Set
BS 105.6	Circular Surcharge Weight	Machined steel plated 10" dia, 10 lbs weight	1 Pc
BS 105.7	Circular Surcharge Weight	Machined steel plated 8" dia, 10 lbs weight	1 Pc
BS 105.8	Circular Surcharge Weight	Machined steel plated 8.5" dia, 20 lbs weight	1 Pc
BS 105.9	Proving Ring	10.000 lbs capacity	1 Set
BG 002/2	Dial Indicator	Range 1" x 0.001"	1 Pc
BG 003/1	Dial Holder	Magnetic	1 Pc

The use of in situ CBR apparatus on road construction contracts enable the bearing capacity soils to be determined quickly efficiently with minimum delay to contracting plant.

Supplied without :

BS.110 Speedy Moisture Tester
BS.043/1 Stop Watch